(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 17 February 2005 (17.02.2005)

PCT

(10) International Publication Number WO 2005/013697 A1

- (51) International Patent Classification7: A21B 3/04, 1/44
- (21) International Application Number:

PCT/AU2004/001049

- (22) International Filing Date: 6 August 2004 (06.08.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 7 August 2003 (07.08.2003) 2003904149

AU

- (71) Applicant (for all designated States except US): MOF-FAT PTY LIMITED [AU/AU]; 740 Springvale Road, Mulgrave, Victoria 3170 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): WILLETT, Paul, Eaton [AU/AU]; Raynbird Road, Narangba, Queensland 4054 (AU).
- (74) Agent: FREEHILLS CARTER SMITH BEADLE; Level 43, 101 Collins Street, Melbourne, Victoria 3000 (AU).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: STEAMING DEVICE FOR BAKER'S OVENS



(57) Abstract: A steaming device (50) for a baker's oven including a steam generation chamber (55), located adjacent at least one heating element (25, 26) in an oven compartment of the baker's oven, the steam generation chamber (55) being closed at one end and having at least one steam outlet at or adjacent the other end; at least one heat sink member (57) in the steam generation chamber (55) to provide a heat source to convert steaming water introduced into the steam generation chamber (55) into steam; and a steaming water pipe (40) having at least one nozzle (41) operable to direct water into the steam generation chamber (55), the steaming water being convertible into steam within the steam generation chamber (55) and releasable to the oven compartment through the at least one steam outlet.